

SPECIAL OPERATIONS VECTOR 3 HH-Series Harness/Container

The Special Operations Vector Harness/Container (SOV3-HH) is designed for HAHO/HALO operations allowing a single operator to carry a full complement of weapons and combat equipment utilizing state-of-the-art technologies, making the SOV3-HH a versatile and essential parachute system for training and operational requirements.

THREE (3) DEPLOYMENT CONFIGURATIONS

The SOV3-HH, with minimal reconfiguration, can support up to three (3) different deployment applications to fit your ever-changing mission parameters.

- Double Bag Static Line (DBSL)
- BOC Hand-Deploy Pilot Chute (HDPC)
- Over-the-Shoulder Ripcord (OTS)

SOV3-HH OPTIONS

- Fully Adjustable Harness with pulley-style main lift web
- Adjustable diagonals, chest, leg straps and waistband
- Six (6) or Eight (8) cargo attachment points
- Seat sling attachment points
- Adjustable leg straps with reversible hardware options
- Zipper attachments for oxygen & utility pouches
- Skyhook RSL with integrated Collins Lanyard
- Ballistic cloth leg pad covers

ADDITIONAL SPECIFICATIONS

Emergency handles - inboard or outboard options available



PRODUCT SPECIFICATIONS

SOV3 HAHO/HALO

SOV3-HH Harness/Container

MAXIMUM SUSPENDED WEIGHT*	490 lb (222 kg)	
MINIMUM DEPLOYMENT ALTITUDE MAIN PARACHUTE**	2,000 - 3,000 ft (610 - 914 m)	
MINIMUM DEPLOYMENT ALTITUDE RESERVE PARACHUTE**	1,500 - 2,000 ft (457 - 610 m)	
MAXIMUM DEPLOYMENT ALTITUDE**	35,000 ft (10,668 m)	
CANOPY ALTERNATIVES	260 - 360 sq ft (24 - 33 sq m)	
PHYSICAL DIMENSIONS	22 x 15 x 5.5 in - 23.5 x 15 x 7 in (56 x 38 x 14 cm) - (60 x 38 x 18 cm)	
HARNESS / CONTAINER WEIGHT	30 - 35 lb (14 - 16 kg)	
RESERVE AAD SETUP	Control unit installed under reserve pin flap, on ring cover, or top of yoke	
RESERVE STATIC LINE	Skyhook RSL with reserve pin attached to lanyard and integrated Collins Lanyard - Split Collins Lanyard option available	
MAIN RISERS	3-Ring, Type 7 with Front Riser Trim Tabs Hard Housing Channels	
MAIN TOGGLES	11 in (28 cm) HAHO toggles with HAHO extensions	
ADJUSTABLE HARNESS	Fully Adjustable MLW, Laterals, Chest & Leg Straps, Bellyband/Waistband	
LEG STRAP HARDWARE	Interchangeable and Adjustable B-12 or Quick Ejector - other types optional	
CONFIGURATIONS	HH 6-Ring	HH 8-Ring
ATTACHMENT POINTS	Six (6) cargo attachment points	Eight (8) cargo attachment points
HANDLE LOCATIONS	In-board emergency handles	Out-board emergency handles
MAIN DEPLOYMENT TYPE	Over-the-Shoulder Ripcord BOC Hand-Deploy, Double Bag Static Line	BOC Hand-Deploy Double Bag Static Line
CONTAINER MATERIAL	Cordura® fabric, denier gauges vary by color option	
COLORS	Black, silver, smoke, navy blue, olive drab green, woodland/digital camouflage, desert camouflage - other colors are available on request	
COMPATIBLE OXYGEN SYSTEMS	Twin 53 cu in, single 80, 120 or 122 cu in	
SPECIAL EQUIPMENT INTERFACES	Zip-On Side Pouches for Oxygen, Radio or Utility Use Seat Sling, Cargo Attachment Points	

* Dependent on main and reserve canopy model and deployment system

** Dependent on canopy choice, deployment system and Skyhook option